

AMENDMENTS TO THE CLAIMS

Please cancel claims 46-73 and 105-111. Please amend claims 6, 18, and 32. Below are the now-pending claims.

1. (Original) A portable card adapted to be used in a card processing system having a data processing station comprising a data storage device adapted to interact with a data processing station when a portable card and a data processing station are moved relative to each other, said data storage device including

a substrate having a predetermined shape;
at least one layer of high density, high coercivity magnetic material for storing magnetic signals; and
a relatively hard, abraadeable protective coating formed on said magnetic material layer and being selected to have a thickness between a maximum thickness which would materially attenuate magnetic signals passing between said magnetic material layer and a transducer and a minimum thickness enabling said protective coating to be abraded by usage in an ambient natural atmosphere operating environment for removing therefrom a known quantity of the protective coating.

2. (Original) The portable card of claim 1 wherein said at least one magnetic material layer is a thin film layer of high density, high coercivity magnetic material having a predetermined magnetic field orientation for storing data.

3. (Original) The portable card of claim 1 wherein protective coating has at least one layer which includes a magnetically permeable, magnetically saturable material.

4. (Original) The portable card of claim 1 wherein protective coating has at least two layers wherein one of said layers includes a magnetically permeable, magnetically saturable material and the other of said layers is a non-magnetic friction reducing layer formed on said one of said layers.

5. (Original) The portable card of claim 1 wherein said at least one magnetic material layer is formed of a high density, high coercivity magnetic material having a predetermined magnetic field orientation and wherein said protective coating has at least one layer which includes a magnetically permeable, magnetically saturable material and wherein said data storage device further includes

Amended

a non-magnetic material layer positioned between the protective coating and said at least one magnetic material layer, said magnetically permeable, magnetically saturable material being responsive through said non-magnetic layer to predetermined magnetic field orientation to produce a magnetic image field in a direction opposite to said predetermined magnetic field orientation.

6. (Currently Amended) The portable card of claim 1 wherein said at least one magnetic material layer is formed of a high density, high coercivity magnetic material having a predetermined magnetic field orientation and wherein said protective coating has at least two layers wherein said one of said layers includes a magnetically permeable, magnetically saturable material and the other of said layers is a non-magnetic abrasion friction reducing layer formed on said one of said layers and wherein said data storage device further includes

a non-magnetic material layer positioned between the protective coating and said at least one magnetic material layer, said magnetically permeable, magnetically saturable material being responsive through said non-magnetic layer to predetermined magnetic field orientation to produce a magnetic image field in a direction opposite to said predetermined magnetic field orientation.

7. (Original) The portable card of claim 1 wherein said protective has an outer surface that is cleanable.

8. (Original) The portable card of claim 1 wherein said substrate has two surfaces and said protective coating is applied to at least one of said two surfaces.

9. (Original) The portable card of claim 1 wherein said substrate has two surfaces and said protective coating is applied to at least one of said two surfaces and wherein said data storage device is located on the other of said two surfaces and said protective coating is applied to at least said data storage device.

10. (Original) The portable card of claim 1 wherein said substrate has two surfaces and wherein said data storage device is located on one of said two surfaces and said protective coating is applied to at least said data storage device.

11. (Original) The portable card of claim 1 having an obverse side and a converse side and wherein said substrate has two surfaces and wherein said data storage device is located on one of said two surfaces and said protective coating is applied to each of said obverse side and converse side.

12. (Original) The portable card of claim 1 wherein said protective coating has an outer surface and further comprises a bonded lubricant layer formed on said outer surface and having a thickness which is less than the thickness of said protective coating.

13. (Original) The portable card of claim 1 wherein said protective coating thickness is in the range of about 700 Angstroms to about 1050 Angstroms.

Amx
14. (Original) The portable card of claim 1 wherein said protective coating thickness includes two substantially parallel layers one of which is formed of a magnetically permeable, magnetically saturable material having a thickness in the range of about 50 Angstroms to about 750 Angstroms and the other of which is a diamond-like carbon layer having a thickness in the range of about 150 Angstroms to about 300 Angstroms.

15. (Original) The portable card of claim 14 wherein said protective coating thickness is in the range of about 700 Angstroms to about 1000 Angstroms.

16. (Original) The portable card of claim 15 wherein said protective coating thickness is about 550 Angstroms.

17. (Original) The portable card of claim 1 wherein said protective coating thickness includes one layer which is formed of a magnetically permeable, magnetically saturable material having a thickness in the range of about 50 Angstroms to about 750 Angstroms and wherein said non-magnetic material layer has a thickness in the range of about 20 Angstroms to about 150 Angstroms.

18. (Currently Amended) The portable card of claim 1 wherein said protective coating thickness includes two substantially parallel layers one of which is formed of a magnetically permeable, magnetically saturable material having a thickness in the range of about 50 Angstroms to about 750 Angstroms and the other of which is a diamond-like carbon layer having a thickness in the range of about 150 Angstroms to about 300 ~~Angstroms~~ Angstroms and wherein said nonmagnetic material layer has a thickness in the range of about 20 ~~Angstroms~~ Angstroms to about 150 ~~Angstroms~~ Angstroms.

19. (Original) The portable card of claim 1 wherein said protective coating thickness includes two substantially parallel layers one of which is formed of a magnetically permeable, magnetically saturable material having a thickness about 400 Angstroms and the other of which is a diamond-like carbon layer having a thickness about 150 Angstroms.

20. (Original) The portable card of claim 1 wherein said protective coating thickness includes two substantially parallel layers one of which is formed of a magnetically permeable, magnetically saturable material having a thickness about 400 Angstroms and the other of which is a diamond-like carbon layer having a thickness about 150 Angstroms and wherein said non-magnetic material layer has a thickness in the range of about 20 Angstroms to about 150 Angstroms.

21. (Original) The portable card of claim 1 wherein said protective coating is adapted to interface with and be responsive to a data processing station when said substrate and data processing station are moved relative to each other to

position said substrate proximate said data processing station to enable data flow therebetween.

22. (Original) The portable card of claim 1 wherein said substrate is moved relative to said data processing station.

23. (Original) The portable card of claim 1 wherein said data processing station is moved relative to said substrate.

Amx
24. (Original) The portable card of claim 1 wherein said data processing station and said substrate are moved relative to each other.

25. (Original) The portable card of claim 1 wherein said substrate is substantially planar and generally rectangular in shape and said data storage device is generally rectangular in shape.

26. (Original) The portable card of claim 25 wherein said substantially planar and generally rectangular shaped substrate including said data storage device is transported past a data processing station.

27. (Original) The portable card of claim 1 wherein said substrate is substantially planar and generally rectangular in shape and said data storage device is generally circular in shape.

28. (Original) The portable card of claim 27 wherein said generally circular shaped data storage device is fixedly mounted within said substantially planar and generally rectangular shaped substrate.

29. (Original) The portable card of claim 28 wherein said substantially planar and generally rectangular shaped substrate including said generally circular shaped data storage device data storage device is rotatable proximate a data processing station.

30. (Original) The portable card of claim 27 wherein said generally circular shaped data storage device is rotatably mounted within said substantially planar and generally rectangular shaped substrate.

Amended
31. (Original) The portable card of claim 30 wherein said substantially planar and generally rectangular shaped substrate including said generally circular shaped data storage device data storage device is positioned proximate a data processing station and said generally circular shaped data storage device data storage device is rotated relative thereto.

32. (Currently Amended) The portable card of claim 2 wherein said thin film layer of magnetic material has an areal density of about 2 megabits per sq. in. to about 10 ~~gigabita~~ gigabits per sq. in.

33. (Original) The portable card of claim 1 wherein said transducer is an inductive head.

34. (Original) The portable card of claim 33 wherein said thin film layer of magnetic material has an areal density of about 2 megabits per sq. in. to about 20 megabits per sq. in.

35. (Original) The portable card of claim 1 wherein said transducer is a thin film head.

36. (Original) The portable card of claim 2 wherein said transducer is a magnetoresistive head and said thin film layer of magnetic material has an areal density of about 20 megabits per sq. in. to about 200 megabits per sq. in.

37. (Original) The portable card of claim 2 wherein said transducer is a giant magnetoresistive (GMR) head and said thin film layer of magnetic material has an areal density of about 20 megabits per sq. in. to about 10 gigabits per sq. in.

Gen
38. (Original) The portable card of claim 2 wherein said thin film layer of magnetic material has a predetermined magnetic field orientation that is substantially perpendicular to at least one surface of said substrate.

39. (Original) The portable card of claim 2 wherein said thin film layer of magnetic material has a predetermined magnetic field orientation that is substantially parallel to a data processing station.

40. (Original) The portable card of claim 2 wherein said thin film layer of magnetic material has a predetermined magnetic field orientation that is at an acute angle to a data processing station.

41. (Original) A portable card of claim 40 wherein the acute angle is in a range of between about 15 degrees and about 45 degrees from a vertical axis to said substrate.

42. (Original) The portable card of claim 2 wherein said at least one thin film layer of high density, high coercivity magnetic material is a sputtered layer.

43. (Original) The portable card of claim 2 wherein said at least one thin film layer of high density, high coercivity magnetic material is a platted layer.

44. (Original) The portable card of claim 2 wherein said at least one thin film layer of high density, high coercivity magnetic material is an oxide layer.

45. (Original) The portable card of claim 2 wherein said at least one thin film layer of high density, high coercivity magnetic material is a web coated layer.

46-73. (Cancelled)

74. (Original) A data storage device comprising at least one layer of high density, high coercivity magnetic material for storing data; and

a relatively hard, abradable protective coating formed on said magnetic material layer and being selected to have a thickness between a maximum thickness which would materially attenuate magnetic signals passing between said magnetic material layer and a transducer and a minimum thickness enabling said protective coating to be abraded by usage in an ambient natural atmosphere operating environment for removing therefrom a known quantity of said protective coating material.

75. (Original) The data storage device of claim 74 wherein said protective coating is of a diamond-like hardness forming a bendable, abradable protective coating.

76. (Original) The data storage device of claim 74 wherein said protective coating is formed of a magnetically permeable,

magnetically saturable material and the known quantity of magnetically permeable, magnetically saturable material removed by usage is to that minimum thickness thereof which is capable of supporting magnetic flux density of a reading signal.

77. (Original) The data storage device of claim 74 wherein said protective coating is formed of a magnetically permeable, magnetically saturable material and the known quantity of magnetically permeable, magnetically saturable material removed by usage is to a thickness at which the magnetically permeable, magnetically saturable material commences to emit a detectable quantity of magnetic flux leakage.

78. (Original) The data storage device of claim 74 wherein the magnetic material layer is formed of a substantially isotropic material.

79. (Original) The data storage device of claim 78 wherein the isotropic material is a magnetic thin film allow including platinum.

80. (Original) The data storage device of claim 74 wherein the magnetic material is formed of an anisotropic material.

81. (Original) The data storage device of claim 80 wherein said magnetic material has a predetermined field of orientation for storing magnetic signals.

82. (Original) The data storage device of claim 80 wherein magnetic material layer has at least one surface and said predetermined field of orientation is in a direction substantially parallel to said one surface.

83. (Original) The data storage device of claim 80 wherein magnetic material layer has at least one surface and said predetermined field of orientation is in a direction substantially perpendicular to said one surface.

84. (Original) The data storage device of claim 80 wherein magnetic material layer has at least one surface and said predetermined field of orientation is in a direction at a predetermined angle to said one surface.

Amx
85. (Original) The data storage device of claim 80 wherein magnetic material layer has at least one surface and said predetermined field of orientation is in a direction at an oblique angle to said one surface.

86. (Original) The data storage device of claim 74 wherein said protective coating has at least one layer which includes a magnetically permeable, magnetically saturable material.

87. (Original) The data storage device of claim 74 wherein said protective coating has at least two layers wherein one of said layers includes a magnetically permeable, magnetically saturable material and the other of said layers is a non-magnetic friction reducing layer formed on said one of said layers.

88. (Original) The data storage device of claim 74 wherein said data storage device further comprises:

a bonded, cleanable lubrication layer formed on said protective coating.

89. (Original) A data storage device comprising:

a substrate having at least one surface;

at least one high density magnetically coercive material layer disposed on said substrate for storing magnetic signals with the coercive material axis of magnetization oriented in a predetermined direction relative to said at least one surface of said substrate; and

Amx
a bendable, diamond like hardness protective coating having a thickness which allows passage of magnetic signals in an ambient natural atmospheric operating environment through said protective layer and between said at least one high density magnetically coercive material layer and a transducer, said protective layer being formed of a material which resists at least one of chemical, magnetic and mechanical degradation of the data storage device.

90. (Original) The data storage device of claim 89 further comprising

at least one non-magnetic material layer disposed on said substrate and between said protective coating and said at least one high density magnetically coercive material layer for defining an exchange break layer.

91. (Original) The data storage device of claim 90 wherein said substrate is a non-magnetic substrate and said protective coating includes

a magnetically permeable, magnetically saturable material disposed on said substrate and being responsive through said exchange break layer to the coercive material axis of magnetization in said predetermined direction to produce a magnetic image field in a direction opposite to said predetermined direction.

92. (Original) The data storage device of claim 90 wherein said protective coating includes said magnetically permeable, magnetically saturable material as a separate independent layer disposed on said exchange break layer.

93. (Original) The data storage device of claim 90 wherein said protective coating includes a non-magnetic friction resisting layer as a separate independent layer disposed on said magnetically permeable, magnetically saturable material layer.

Acry
94. (Original) The data storage device of claim 89 wherein said predetermined direction is orientated substantially parallel to said at least one surface of said substrate.

95. (Original) The data storage device of claim 89 wherein said predetermined direction is orientated at an acute angle to said at least one surface of said substrate.

96. (Original) The data storage device of claim 89 wherein said predetermined direction is orientated substantially perpendicular to said. at least one surface of said substrate.

97. (Original) A magnetically encoded card comprising
a non-magnetic substrate having at least one surface,
a thin film, high density magnetically coercive material
disposed on said substrate for storing magnetic signals with the
coercive material axis of magnetization oriented in a
predetermined direction relative to said at least on surface of
said substrate;
a non magnetic material disposed on said substrate for defining
an exchange break layer; and

a relatively hard, bendable, abradeable protective coating formed on said magnetic material layer and being selected to have a thickness between a maximum thickness which would materially attenuate magnetic signals passing between said magnetic material layer and a transducer and a minimum thickness enabling said protective coating to be abraded by usage in an ambient natural atmosphere operating environment for removing therefrom a known quantity of the protective coating.

Amend
98. (Original) The magnetically encoded card of claim 97 wherein said protective coating is formed on said substrate in a direction substantially normal to said exchange break layer, said protective coating including a magnetically permeable, magnetically saturable material disposed on said substrate and being responsive through said exchange break layer and said magnetically saturable material to the coercive material axis of magnetization to produce a magnetic image field in a direction to facilitate passage of magnetic signals in an ambient natural atmospheric operating environment through said exchange break layer and said magnetically saturable material, said coercive material having said axis of magnetization in said predetermined direction.

99. (Original) The magnetically encoded card of claim 97 wherein said protective coating includes said magnetically permeable, magnetically saturable material as an independent layer disposed on said substrate.

100. (Original) The magnetically encoded card of claim 97 wherein said protective coating includes a non-magnetic friction resisting material as a separate layer disposed on said magnetically permeable, magnetically saturable material.

101. (Original) The magnetically encoded card of claim 97 wherein said predetermined direction is orientated substantially parallel to said at least one surface of said substrate.

102. (Original) The magnetically encoded card of claim 97 wherein said predetermined direction is orientated at an acute angle to said at least one surface of said substrate.

Ames
103. (Original) The data storage device of claim 97 wherein said predetermined direction is orientated substantially perpendicular to said at least one surface of said substrate.

104. (Original) The magnetically encoded card of claim 97 wherein the magnetically coercive material is at least 1,000 Oersteds and wherein said magnetically permeable, magnetically saturable material is less than about 100 Oersteds.

105-111. (Cancelled)

112. (Original) A data storage device comprising
at least one thin film layer of high density, high coercivity magnetic material having a predetermined magnetic field orientation for storing data; and

a relatively hard, abraadeable protective coating formed on said magnetic material layer and being selected to have a thickness between a maximum thickness which would materially attenuate magnetic signals passing between said at least one thin film layer and a transducer and a minimum thickness enabling said protective coating to be abraded by usage in an ambient natural atmosphere operating environment for removing therefrom a known quantity of the protective coating, said data storage device being adapted to interface with and be responsive

to a transducer when said data storage device and said transducer are moved relative to each other to enable data flow therebetween.

113. (Original) The data storage device of claim 111 wherein said protective coating has at least one layer which includes a magnetically permeable, magnetically saturable material.

Am
114. (Original) The data storage device of claim 112 wherein said protective coating has at least two layers wherein one of said layers includes a magnetically permeable, magnetically saturable material and the other of said layers is a non-magnetic abrasion resisting layer formed on said one of said layers.

115. (Original) The data storage device of claim 112 wherein said data storage device further comprises
a bonded, cleanable lubrication layer applied to outer surface of said protective coating, said bonded, cleanable lubrication layer having a thickness which is less than the thickness of said protective coating.
